

Datasheet for: 110316




T-connection POM, for hose exterior Ø 8 mm

T-connection POM, for hose exterior Ø 8 mm, Working pressure max. 16 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	69.008
-------------	--------

Article number	110316
----------------	--------

EAN/barcode	 4047322113311
-------------	--

Your price	3,44 € / Stk
------------	--------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	8 mm
L1	42.0 mm
L2	21.0 mm
Material	Acetal polymer (POM)
Max. operating temperature in air	70 °C
Max. operating temperature in water	70 °C
Max. working pressure	16 bar
Min. operating temperature in air	-20 °C
Min. operating temperature in water	1 °C
Page No.	HK941

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Max. working pressure</i>	<i>Price</i>
110316	8 mm	16 bar	3,44 € / Stk
110313	4 mm	16 bar	3,03 € / Stk
110314	5 mm	16 bar	3,20 € / Stk
110315	6 mm	16 bar	3,29 € / Stk
110317	10 mm	10 bar	4,33 € / Stk
110318	12 mm	10 bar	5,02 € / Stk
110319	15 mm	10 bar	8,71 € / Stk
110320	18 mm	10 bar	12,46 € / Stk
110321	22 mm	10 bar	13,16 € / Stk
110322	28 mm	10 bar	22,13 € / Stk

More Pictures

