

Datasheet for: 110327



T-reducer connector POM, for hose exterior Ø1 22 mm / Ø2 15 mm

T-reducer connector POM, for hose exterior Ø1 22 mm, for hose exterior Ø2 15 mm, Working pressure max. 10 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	70.022-15
Article number	110327
EAN/barcode	 404732220491
Your price	12,35 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D. 1	22.0 mm
For tube O.D. 2	15.0 mm
L1	90.6 mm
L2	41.6 mm
Material	Acetal polymer (POM)
Max. operating temperature in air	70 °C
Max. operating temperature in water	70 °C
Max. working pressure	10 bar
Min. operating temperature in air	-20 °C
Min. operating temperature in water	1 °C
Page No.	HK942

Variants

Article number	For tube O.D. 1	Price
110327	22.0 mm	12,35 € / Stk
110326	18.0 mm	12,35 € / Stk

More Pictures

