


Datasheet for: 110856



Straight screw-in fitting, G 3/8 o., for hose 4/6 mm, AF 22, PP

Straight screw-in fitting, G 3/8 o., for hose 4/6 mm, AF 22, Working pressure max. 10 bar (20 °C)/max. 2.5 bar (90 °C), PP . Chemically resistant to almost all inorganic acids and bases, even in high concentrations and at temperatures greater than 90 °C.

Type number	120.21-PP
Article number	110856
EAN/barcode	 4047322021777
Your price	8,09 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For hose	4/6 mm
L1	38.5 mm
L2	12.0 mm
Material	Polypropylene (PP)
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 90 °C	2.5 bar
Max. operating temperature	90 °C
Page No.	HK745
Thread	G 3/8
a/f	22 mm

Variants

Article number	Thread	For hose	a/f	Price
110856	G 3/8	4/6 mm	22 mm	8,09 € / Stk

Variants

Article number	Thread	For hose	a/f	Price
110851	G 1/8	9/12 mm	22 mm	16,26 € / Stk
110855	G 1/4	9/12 mm	22 mm	15,59 € / Stk
110854	G 1/4	8/10 mm	19 mm	9,00 € / Stk
110852	G 1/4	4/6 mm	17 mm	3,86 € / Stk
110849	G 1/8	6/8 mm	17 mm	6,54 € / Stk
110860	G 1/2	4/6 mm	27 mm	9,68 € / Stk
110850	G 1/8	8/10 mm	19 mm	9,30 € / Stk
110853	G 1/4	6/8 mm	17 mm	6,42 € / Stk
110857	G 3/8	6/8 mm	22 mm	12,95 € / Stk
110859	G 3/8	9/12 mm	22 mm	17,58 € / Stk
110862	G 1/2	8/10 mm	27 mm	11,54 € / Stk
110858	G 3/8	8/10 mm	22 mm	11,88 € / Stk
110863	G 1/2	9/12 mm	27 mm	19,39 € / Stk
110861	G 1/2	6/8 mm	27 mm	11,21 € / Stk
110848	G 1/8	4/6 mm	14 mm	2,99 € / Stk

More Pictures

