


Datasheet for: 107766



GEKA threaded piece, rigid, bright brass, G 1 1/2 interior

GEKA threaded piece, rigid, bright brass, G 1 1/2 interior, Operating pressure max. 40 bar, Medium / ambient temp. -10 °C to 90 °C . Claw couplings (claw distance: 40 mm) made of brass for water, industrial, mortar, suction and discharge hoses. Suitable for a wide range of applications, e.g. industrial plant engineering, civil and structural engineering, environmental engineering, manual trades, domestic water engineering, horticulture and landscaping, agriculture and forestry, etc. Available in a rigid or 360° swivelling version. The two systems can also be easily coupled to one another!

Type number	K 116
Article number	107766
EAN/barcode	 4047322133050
Your price	8,16 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1 1/2 IT
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK607
Sealant	NBR

Variants

Article number	Connection	Price
107766	G 1 1/2 IT	8,16 € / Stk
107761	G 3/8 IT	4,58 € / Stk
107762	G 1/2 IT	4,26 € / Stk
107763	G 3/4 IT	4,33 € / Stk
107764	G 1 IT	4,58 € / Stk
107765	G 1 1/4 IT	7,02 € / Stk
107760	G 1/4 IT	4,80 € / Stk