


Datasheet for: 156653



Mist oiler »FUTURA«, Metal container, Viewing tube, Size 4, G 1

Mist oiler »FUTURA«, with metal container and viewing tube, Size 4, G 1, Input pressure max. 16 bar, Temp. -10 °C to 50 °C. Oil-mist lubricators with excellent flow rates in modern design. These devices can be used to top up oil automatically. A hose must be connected to the threaded nipple on the oil bowl for this purpose. When the oil filling button on the top of the device is pressed, a Venturi nozzle opens and sucks oil into the bowl under vacuum.

Type number	FU 6202-M
Article number	156653
EAN/barcode	 4047322629669
Your price	131,55 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	85.0 mm
B	271.0 mm
Bowl	Metal container with viewing tube
C	88.0 mm
Connecting thread	Material: Die-cast zinc
Flow rate	14000 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	PA66 GF60
Max. input pressure	16 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. temperature range	-10 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	HK042
Sealant	NBR
Series	FUTURA
Sight dome	PC
Size	4
Thread	G 1

Variants

Article number	Thread	Flow rate	Size	Price
156653	G 1	14000 l/min	4	131,55 € / Stk
139515	G 1/2	8000 l/min	2	85,65 € / Stk
139514	G 3/8	8000 l/min	2	85,65 € / Stk
156652	G 3/4	14000 l/min	4	131,55 € / Stk
156650	G 1/4	2750 l/min	1	59,91 € / Stk
156651	G 3/8	2750 l/min	1	59,91 € / Stk

More Pictures

