


Datasheet for: 100991



Special filter »Standard«, PC container, 0.01 µm, Size 3, G 1/2

Special filter »Standard« with PC container, 0.01 µm, Size 3, G 1/2, Input pressure max. 16 bar, Medium / ambient temp. max. 50 °C . For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Type number	685 K-HA
Article number	100991
EAN/barcode	 4047322359115
Your price	102,90 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	79.0 mm
Bowl	Polycarbonate container
C	18.0 mm
Condensate drain	Semi-automatic
D	168.4 mm
DN	15.0
Efficiency	99.999 %
Filter rating	0.01 µm
Flow rate	1250 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
H	50.0 mm
Housing	Die-cast zinc, painted silver
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Page No.	HK127
Series	Standard
Size	3
Thread	G 1/2

Variants

Article number	Thread	Flow rate	Size	DN	Condensate drain	Price
100991	G 1/2	1250 l/min	3	15.0	Semi-automatic	102,90 € / Stk
100992	G 3/4	7000 l/min	4	20.0	Manuel	253,13 € / Stk
100993	G 1	7000 l/min	4	25.0	Manuel	250,68 € / Stk
100990	G 3/8	720 l/min	2	10.0	Semi-automatic	74,99 € / Stk
100988	G 1/4	380 l/min	1	6.0	Semi-automatic	52,84 € / Stk
100989	G 3/8	380 l/min	1	6.0	Semi-automatic	68,98 € / Stk

More Pictures

