


Datasheet for: 102526



Capsule pressure gauge, radial bottom, G 1/2, - 250 mbar, Ø 100

Capsule pressure gauge, 10 times overload-safe, Connection radial bottom, G 1/2, Goods class 1.6, Measuring range 0-250 mbar, Ø100 . Overpressure safety 10x FSD, with zero correction.

Type number	6844
Article number	102526
EAN/barcode	 4047322112703
Your price	130,46 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy class	1.6
Applications	For gaseous, dry, non-corrosive media
Connection	G 1/2
Connection position	radial on bottom
Diameter	100 mm
Front glass	Flat instrument glass
Housing	CrNi steel
Max. ambient temperature	60 °C
Max. medium temperature	100 °C
Measuring element	Copper alloy
Measuring range max. mbar	250.0
Measuring range min. mbar	0.0
Min. ambient temperature	-20 °C
Movement	Copper alloy
Page No.	HK220
Scale graduation in the mbar area	5.0 mbar
Type	612.20
Version	Capsule-type pressure gauge

Variants

Article number	Type	Housing	Measuring range max. mbar	Diameter	Connection	Price
102526	612.20	CrNi steel	250.0	100 mm	G 1/2	130,46 € / Stk
102517	611.10	Steel, black	40.0	63 mm	G 1/4	102,97 € / Stk
102518	611.10	Steel, black	60.0	63 mm	G 1/4	102,97 € / Stk
102519	611.10	Steel, black	100.0	63 mm	G 1/4	102,97 € / Stk
102520	611.10	Steel, black	160.0	63 mm	G 1/4	102,97 € / Stk
102521	611.10	Steel, black	250.0	63 mm	G 1/4	102,97 € / Stk
102522	612.20	CrNi steel	40.0	100 mm	G 1/2	130,46 € / Stk
102523	612.20	CrNi steel	60.0	100 mm	G 1/2	130,46 € / Stk
102524	612.20	CrNi steel	100.0	100 mm	G 1/2	130,46 € / Stk
102525	612.20	CrNi steel	160.0	100 mm	G 1/2	130,46 € / Stk