

Datasheet for: 101004



Special filter »Standard« Metal container, 0.01 μm , Size 4, G 3/4

Special filter »Standard« with metal container, 0.01 μm , Size 4, G 3/4, Input pressure max. 25 bar, Med. / ambient temp. max. 50°C . For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Type number	695 M
Article number	101004
EAN/barcode	 4047322113410
Your price	322,79 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	133.0 mm
Bowl	Metal container
C	36.0 mm
Condensate drain	Manuel
D	206.0 mm
DN	20.0
Efficiency	99.999 %
Filter rating	0.01 μm
Flow rate	7000 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
H	134.0 mm
Housing	Die-cast zinc, painted silver
Max. ambient temperature	50 °C
Max. input pressure	25 bar
Max. medium temperature	50 °C
Page No.	HK127
Series	Standard
Size	4
Thread	G 3/4

Variants

Article number	Thread	Flow rate	Size	DN	Price
101004	G 3/4	7000 l/min	4	20.0	322,79 € / Stk
101000	G 1/4	380 l/min	1	6.0	56,27 € / Stk
101001	G 3/8	380 l/min	1	6.0	65,47 € / Stk
101002	G 3/8	720 l/min	2	10.0	79,44 € / Stk
101003	G 1/2	1250 l/min	3	15.0	110,66 € / Stk
101005	G 1	7000 l/min	4	25.0	349,81 € / Stk

More Pictures

