

Datasheet for: 100999



Special filter »Standard« Protective cage, 0.01 µm, Size 4, G 1

Special filter »Standard« with polycarbonate container and protective cage, 0.01 µm, Size 4, G 1, Input pressure max. 16 bar. For all applications with particularly strict compressed air purity requirements. The separating efficiency of these filters permits very fine oil vapour particles and micro-fine suspended particles to be filtered. A standard filter should always be connected upstream to trap coarse impurities and protect the micro-filter inserts.

Type number	696 S
Article number	100999
EAN/barcode	 4047322113496
Your price	303,45 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	133.0 mm
Bowl	Polycarbonate container with protective cage
C	36.0 mm
Condensate drain	Manuel
D	206.0 mm
DN	25.0
Efficiency	99.999 %
Filter rating	0.01 µm
Flow rate	7000 l/min
Flow rate measurement	At P ₂ = 6 bar and pressure drop Δ _p = 1 bar
H	120.0 mm
Housing	Die-cast zinc, painted silver
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Page No.	HK127
Series	Standard
Size	4
Thread	G 1

Variants

Article number	Thread	Flow rate	Size	DN	Condensate drain	Price
100999	G 1	7000 l/min	4	25.0	Manuel	303,45 € / Stk
100994	G 1/4	380 l/min	1	6.0	Semi-automatic	69,54 € / Stk
100995	G 3/8	380 l/min	1	6.0	Semi-automatic	81,19 € / Stk
100996	G 3/8	720 l/min	2	10.0	Semi-automatic	93,77 € / Stk
100997	G 1/2	1250 l/min	3	15.0	Semi-automatic	128,94 € / Stk
100998	G 3/4	7000 l/min	4	20.0	Manuel	303,45 € / Stk

More Pictures

