

## Datasheet for: 101050



### Service unit 2-part »Standard« with PC container, Size 4, G 3/4

Service unit 2-part »Standard« with polycarbonate container, Size 4, G 3/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar . Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

|                |                                                                                                    |
|----------------|----------------------------------------------------------------------------------------------------|
| Type number    | 865 K                                                                                              |
| Article number | 101050                                                                                             |
| EAN/barcode    | <br>4047322121804 |
| Your price     | 371,90 € / Stk                                                                                     |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                             |                                                                      |
|-----------------------------|----------------------------------------------------------------------|
| A                           | 220.0 mm                                                             |
| B                           | 452.0 mm                                                             |
| Bowl                        | Polycarbonate container                                              |
| C                           | 190.6 mm                                                             |
| Condensate drain            | Semi-automatic                                                       |
| DN                          | 20.0                                                                 |
| Filter rating               | 40.0 µm                                                              |
| Flow rate                   | 4000 l/min                                                           |
| Flow rate measurement       | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Housing                     | Die-cast zinc / aluminium, painted silver                            |
| Max. ambient temperature    | 60 °C                                                                |
| Max. control range          | 10.0 bar                                                             |
| Max. input pressure         | 16 bar                                                               |
| Max. medium temperature     | 60 °C                                                                |
| Min. control range          | 0.5 bar                                                              |
| Page No.                    | HK130                                                                |
| Pressure gauge display max. | 16.0 bar                                                             |

|                             |          |
|-----------------------------|----------|
| Pressure gauge display min. | 0.0 bar  |
| Pressure gauge Ø            | 63 mm    |
| Sealant                     | NBR      |
| Series                      | Standard |
| Sight dome                  | PA       |
| Size                        | 4        |
| Thread                      | G 3/4    |

## Variants

| Article number | Thread | Filter rating | Flow rate  | Size | DN   | Price          |
|----------------|--------|---------------|------------|------|------|----------------|
| 101050         | G 3/4  | 40.0 µm       | 4000 l/min | 4    | 20.0 | 371,90 € / Stk |
| 101046         | G 1/4  | 5.0 µm        | 600 l/min  | 1    | 6.0  | 85,95 € / Stk  |
| 101047         | G 3/8  | 5.0 µm        | 600 l/min  | 1    | 6.0  | 85,95 € / Stk  |
| 101048         | G 3/8  | 40.0 µm       | 800 l/min  | 2    | 10.0 | 155,39 € / Stk |
| 101049         | G 1/2  | 5.0 µm        | 2100 l/min | 3    | 15.0 | 155,39 € / Stk |
| 101051         | G 1    | 40.0 µm       | 4000 l/min | 4    | 25.0 | 371,90 € / Stk |
| 174098         | G 3/4  | 40.0 µm       | 4000 l/min | 4    | 20.0 | 371,90 € / Stk |
| 174099         | G 1    | 40.0 µm       | 4000 l/min | 4    | 25.0 | 371,90 € / Stk |

## More Pictures

