

## Fittings Pneufit C

Ø A = matching tube outer diameter. B = Thread (G for parallel, R for conical).

Drawings with complete dimensions can be found on the internet under [www.maedler.de](http://www.maedler.de)

### Straight Unions

Product No.	Ø A mm
866 104 00	4
866 106 00	6
866 108 00	8



### Swivel Elbow Adaptors with Taper Thread

Product No.	Ø A mm	B
866 404 18	4	R1/8
866 404 14	4	R1/4
866 406 18	6	R1/8
866 406 14	6	R1/4
866 408 18	8	R1/8
866 408 14	8	R1/4



### Straight Adaptors with Taper Thread

Product No.	Ø A mm	B
866 204 18	4	R1/8
866 204 14	4	R1/4
866 206 18	6	R1/8
866 206 14	6	R1/4
866 208 18	8	R1/8
866 208 14	8	R1/4



### Swivel Elbow Adaptors with Cylindrical Thread

Product No.	Ø A mm	B
866 504 18	4	G1/8
866 504 14	4	G1/4
866 506 18	6	G1/8
866 506 14	6	G1/4
866 508 18	8	G1/8
866 508 14	8	G1/4



### Straight Adaptors with Cylindrical Thread

Product No.	Ø A mm	B
866 304 18	4	G1/8
866 304 14	4	G1/4
866 306 18	6	G1/8
866 306 14	6	G1/4
866 308 18	8	G1/8
866 308 14	8	G1/4



### Swivel Tee-Adaptors with Cylindrical Thread

Product No.	Ø A mm	B
866 604 18	4	G1/8
866 604 14	4	G1/4
866 606 18	6	G1/8
866 606 14	6	G1/4
866 608 18	8	G1/8
866 608 14	8	G1/4



### Union Elbows

Product No.	Ø A mm
866 124 00	4
866 126 00	6
866 128 00	8



### Pneufit C Fittings

- Housing made primarily from plastic.
- Low cost.
- Modern design.
- Increasing distribution.
- Operating pressure: max. 10 bar.
- Vacuum: max. -1 bar.