

Datasheet for: 110829


Straight hose connection, for hose 6/8 mm, AF 19, PA

Straight hose connection, for hose 6/8 mm, AF 19, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA. Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	140.02
Article number	110829
EAN/barcode	 4047322027267
Your price	2,53 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	6/8 mm
Knurled nut	Polypropylene (PP)
L1	49.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK743
Screw fitting body	Polyamide (PA)
a/f	19 mm

Variants

Article number	For hose	a/f	Price
110829	6/8 mm	19 mm	2,53 € / Stk

Variants

Article number	For hose	a/f	Price
110828	4/6 mm	14 mm	1,50 € / Stk
110830	8/10 mm	22 mm	3,51 € / Stk
110831	9/12 mm	24 mm	7,31 € / Stk

More Pictures

