


Datasheet for: 113145


Cap 300, IT, Rp 1, black malleable cast iron

Cap 300, IT, Rp 1, Operating temperature -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFK 300-10
Article number	113145
EAN/barcode	 4047322253604
Your price	1,51 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK862
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp 1

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113145	Rp 1	1,51 € / Stk
113148	Rp 2	4,67 € / Stk
113147	Rp 1 1/2	2,87 € / Stk
113146	Rp 1 1/4	2,23 € / Stk
113144	Rp 3/4	1,11 € / Stk
113142	Rp 3/8	0,90 € / Stk
113141	Rp 1/4	0,90 € / Stk
113143	Rp 1/2	0,97 € / Stk
113149	Rp 2 1/2	9,35 € / Stk
113150	Rp 3	10,59 € / Stk