


Datasheet for: 133721


Bushing 270, IT/IT, Rp 1, black malleable iron fitting

Bushing 270, IT/IT, Rp 1, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFM 270-10-S
Article number	133721
EAN/barcode	 4047322481748
Your price	1,52 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK869
Standard	acc. ISO 7-1
thread	Black
Surface	Rp 1
Thread	

Variants

Article number	Thread	Price
133721	Rp 1	1,52 € / Stk

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133720	Rp 3/4	1,13 € / Stk
133722	Rp 1 1/4	2,43 € / Stk
133719	Rp 1/2	0,81 € / Stk
133726	Rp 3	16,17 € / Stk
133718	Rp 3/8	0,93 € / Stk
133717	Rp 1/4	0,95 € / Stk
133724	Rp 2	4,85 € / Stk
133723	Rp 1 1/2	3,23 € / Stk
133725	Rp 2 1/2	13,09 € / Stk