


Datasheet for: 133741


Reducing piece 241, R 1 1/2 ET, Rp 1 IT

Reducing piece 241, R 1 1/2 ET, Rp 1 IT black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFR 241-11210-S
Article number	133741
EAN/barcode	 4047322482004
Your price	2,55 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK869
Standard	acc. ISO 7-1
thread	Black
Surface	R 1 1/2
Thread 1	Rp 1
Thread 2	

Variants

<i>Article number</i>	<i>Thread 1</i>	<i>Thread 2</i>	<i>Price</i>
133741	R 1 1/2	Rp 1	2,55 € / Stk
133743	R 2	Rp 3/4	4,31 € / Stk
133736	R 1 1/4	Rp 1/2	1,94 € / Stk
133731	R 3/4	Rp 3/8	1,00 € / Stk
133747	R 2 1/2	Rp 2	7,12 € / Stk
133740	R 1 1/2	Rp 3/4	2,55 € / Stk
133729	R 1/2	Rp 3/8	0,79 € / Stk
133735	R 1	Rp 3/4	1,20 € / Stk
133733	R 1	Rp 3/8	1,62 € / Stk
133727	R 3/8	Rp 1/4	0,93 € / Stk
133748	R 3	Rp 1 1/2	11,55 € / Stk
133746	R 2	Rp 1 1/2	4,04 € / Stk
133732	R 3/4	Rp 1/2	0,84 € / Stk
133744	R 2	Rp 1	4,04 € / Stk
133742	R 2	Rp 1/2	4,55 € / Stk
133734	R 1	Rp 1/2	1,20 € / Stk
133730	R 3/4	Rp 1/4	1,24 € / Stk
133728	R 1/2	Rp 1/4	0,81 € / Stk
133739	R 1 1/2	Rp 1/2	2,55 € / Stk
133737	R 1 1/4	Rp 3/4	1,94 € / Stk
133738	R 1 1/4	Rp 1	1,94 € / Stk
133745	R 2	Rp 1 1/4	4,04 € / Stk