


## Datasheet for: 113109


**Double threaded nipple 280, ET/ET, R 1, black malleable cast iron**

Double threaded nipple 280, ET/ET, R 1, Operating temperature -20°C to 300°C, black malleable cast iron, Hot-dip galvanised . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFD 280-10
Article number	113109
EAN/barcode	 4047322253857
Your price	1,54 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK861
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	R 1

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113109	R 1	1,54 € / Stk
113106	R 3/8	1,29 € / Stk
113107	R 1/2	0,87 € / Stk
113110	R 1 1/4	2,67 € / Stk
113111	R 1 1/2	3,09 € / Stk
113112	R 2	5,10 € / Stk
113105	R 1/4	1,29 € / Stk
113108	R 3/4	1,07 € / Stk
113114	R 3	12,21 € / Stk
113113	R 2 1/2	9,69 € / Stk