


Datasheet for: 110813



Angled screw-on fitting G 1/4 i., for hose 4/6 mm, PA

Angled screw-on fitting G 1/4 i., for hose 4/6 mm, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA .
 Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	150.11
Article number	110813
EAN/barcode	 4047322029377
Your price	2,58 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	4/6 mm
Knurled nut	Polypropylene (PP)
L1	29.0 mm
L2	20.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK742
Screw fitting body	Polyamide (PA)
Thread	G 1/4

Variants

Article number	Thread	For hose	Price
110813	G 1/4	4/6 mm	2,58 € / Stk

Variants

Article number	Thread	For hose	Price
110811	G 1/8	4/6 mm	2,21 € / Stk
110812	G 1/8	6/8 mm	3,34 € / Stk
110814	G 1/4	6/8 mm	4,26 € / Stk
110815	G 1/4	8/10 mm	6,32 € / Stk

More Pictures

