

Datasheet for: 112902


Bracket 92, 90°, IT/ET, Rp/R 3/4, black malleable cast iron

Bracket 92, 90°, IT/ET, Rp/R 3/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

| | |
|----------------|--|
| Type number | TFW 92-34 |
| Article number | 112902 |
| EAN/barcode |  4047322252201 |
| Your price | 1,61 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|------------------------|---|
| Material | Black malleable iron B350-10, design symbol A |
| Max. temperature range | 300 °C |
| Min. temperature range | -20 °C |
| Page No. | HK856 |
| Standard thread | acc. ISO 7-1 |
| Surface | Hot dip galvanised |
| Thread | Rp/R 3/4 |

Variants

| <i>Article number</i> | <i>Thread</i> | <i>Price</i> |
|-----------------------|---------------|---------------|
| 112902 | Rp/R 3/4 | 1,61 € / Stk |
| 112900 | Rp/R 3/8 | 1,41 € / Stk |
| 112901 | Rp/R 1/2 | 1,11 € / Stk |
| 112905 | Rp/R 1 1/2 | 6,22 € / Stk |
| 112906 | Rp/R 2 | 8,56 € / Stk |
| 112903 | Rp/R 1 | 2,51 € / Stk |
| 112904 | Rp/R 1 1/4 | 4,53 € / Stk |
| 112899 | Rp/R 1/4 | 1,41 € / Stk |
| 112907 | Rp/R 2 1/2 | 20,99 € / Stk |
| 112908 | Rp/R 3 | 28,75 € / Stk |