

Datasheet for: 110837


T-hose fitting, for hose 6/8 mm, PA

T-hose fitting, for hose 6/8 mm, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA . Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	140.22
Article number	110837
EAN/barcode	 4047322027496
Your price	3,73 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	6/8 mm
Knurled nut	Polypropylene (PP)
L1	62.0 mm
L2	31.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK743
Screw fitting body	Polyamide (PA)

Variants

Article number	For hose	Price
110837	6/8 mm	3,73 € / Stk

Variants

<i>Article number</i>	<i>For hose</i>	<i>Price</i>
110836	4/6 mm	2,31 € / Stk
110838	8/10 mm	5,02 € / Stk
110839	9/12 mm	10,08 € / Stk

More Pictures

