

## Datasheet for: 111524


**Socket, reduced, G 1/4 i., G 1/2 i., AF 24, nickel-plated brass**

Socket, reduced, G 1/4 i., G 1/2 i., AF 24, nickel-plated brass, Max. working pressure 25 bar, Max. operating temperature 150 °C . Suitable for air, water, oil, steam, etc.

Type number	231.05-N
Article number	111524
EAN/barcode	 4047322054706
Your price	2,64 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

L1	28.5 mm
Material	Nickel-plated brass CW614N
Max. operating temperature	150 °C
Max. working pressure	25 bar
Page No.	HK779
Thread 1	G 1/4
Thread 2	G 1/2
a/f	24 mm

**Variants**

Article number	Thread 1	Thread 2	a/f	Price
111524	G 1/4	G 1/2	24 mm	2,64 € / Stk
111520	M5	G 1/8	14 mm	1,02 € / Stk
111521	G 1/8	G 1/4	17 mm	1,20 € / Stk
111522	G 1/8	G 3/8	22 mm	1,84 € / Stk

## Variants

Article number	Thread 1	Thread 2	a/f	Price
111523	G 1/4	G 3/8	22 mm	2,00 € / Stk
111525	G 3/8	G 1/2	24 mm	2,69 € / Stk
111526	G 1/2	G 3/4	32 mm	4,30 € / Stk
111528	G 1	G 3/4	38 mm	6,87 € / Stk
111527	G 1/2	G 1/8	24 mm	4,33 € / Stk

## More Pictures

