

Datasheet for: 112952

Bracket 121, 45°, IT/ET, Rp/R 3/8, black malleable cast iron


Bracket 121, 45°, IT/ET, Rp/R 3/8, Operating temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 121-38
Article number	112952
EAN/barcode	 4047322252539
Your price	2,67 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK857
Standard	acc. ISO 7-1
thread	Hot dip galvanised
Surface	Rp/R 3/8
Thread	

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112952	Rp/R 3/8	2,67 € / Stk
112958	Rp/R 2	12,57 € / Stk
112954	Rp/R 3/4	3,23 € / Stk
112953	Rp/R 1/2	2,34 € / Stk
112956	Rp/R 1 1/4	8,62 € / Stk
112955	Rp/R 1	4,85 € / Stk
112957	Rp/R 1 1/2	9,35 € / Stk