

Datasheet for: 110264


Straight screw-in fitting POM, G 1/4 o., for hose exterior Ø 5 mm

Straight screw-in fitting POM, G 1/4 o., for hose exterior Ø 5 mm, Working pressure max. 16 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	65.014-5
Article number	110264
EAN/barcode	 4047322109772
Your price	1,75 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	5 mm
L1	24.1 mm
Material	Acetal polymer (POM)
Max. operating temperature in air	70 °C
Max. operating temperature in water	70 °C
Max. working pressure	16 bar
Min. operating temperature in air	-20 °C
Min. operating temperature in water	1 °C
Page No.	HK939
Thread	G 1/4
a/f	17 mm

Variants

<i>Article number</i>	<i>Thread</i>	<i>For tube O.D.</i>	<i>Max. working pressure</i>	<i>Price</i>
110264	G 1/4	5 mm	16 bar	1,75 € / Stk
110259	G 1/8	4 mm	16 bar	1,44 € / Stk
110260	G 1/8	5 mm	16 bar	1,50 € / Stk
110261	G 1/8	6 mm	16 bar	1,50 € / Stk
110262	G 1/8	8 mm	16 bar	1,55 € / Stk
110263	G 1/4	4 mm	16 bar	1,75 € / Stk
110265	G 1/4	6 mm	16 bar	1,99 € / Stk
110266	G 1/4	8 mm	16 bar	1,93 € / Stk
110267	G 1/4	10 mm	10 bar	2,46 € / Stk
110268	G 3/8	8 mm	16 bar	2,05 € / Stk
110269	G 3/8	10 mm	10 bar	2,70 € / Stk
110270	G 3/8	12 mm	10 bar	3,33 € / Stk
110271	G 1/2	10 mm	10 bar	3,44 € / Stk
110272	G 1/2	12 mm	10 bar	3,70 € / Stk
110273	G 1/2	15 mm	10 bar	6,83 € / Stk
110274	G 1/2	18 mm	10 bar	6,83 € / Stk
110275	G 3/4	22 mm	10 bar	6,83 € / Stk
135951	G 3/4	15 mm	10 bar	7,67 € / Stk
135950	G 3/8	15 mm	10 bar	4,32 € / Stk
135952	G 1	28 mm	10 bar	11,20 € / Stk

More Pictures

