

Datasheet for: 108898


Push-in L-fitting »metallica« rotating, G 1/8 o., hose ext. Ø 8

Push-in L-fitting »metallica«, rotating, G 1/8 o., for hose exterior Ø 8 mm, Working pressure max. 16 bar, nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	854.018-8
Article number	108898
EAN/barcode	 4047322279314
Your price	3,91 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	8 mm
L1	24.0 mm
L2	20.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK713
Series	metallica
Sleeve	Nickel-plated brass
Thread	G 1/8
a/f	13 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
108898	G 1/8	8 mm	13 mm	3,91 € / Stk
108905	G 3/8	10 mm	16 mm	5,95 € / Stk
108904	G 3/8	8 mm	13 mm	4,91 € / Stk
108894	M5	4 mm	9 mm	3,87 € / Stk
108902	G 1/4	10 mm	16 mm	5,51 € / Stk
108901	G 1/4	8 mm	13 mm	4,08 € / Stk
108899	G 1/4	4 mm	13 mm	3,87 € / Stk
108907	G 1/2	10 mm	16 mm	7,96 € / Stk
108900	G 1/4	6 mm	13 mm	3,75 € / Stk
108895	M5	6 mm	9 mm	4,13 € / Stk
108896	G 1/8	4 mm	13 mm	3,43 € / Stk
108897	G 1/8	6 mm	13 mm	3,43 € / Stk
108908	G 1/2	12 mm	20 mm	9,56 € / Stk
108903	G 1/4	12 mm	16 mm	7,81 € / Stk
108906	G 3/8	12 mm	20 mm	8,12 € / Stk
136777	G 3/8	16 mm	20 mm	30,81 € / Stk
136778	G 1/2	16 mm	20 mm	32,20 € / Stk
137009	G 1/2	14 mm	20 mm	8,43 € / Stk
137008	G 3/8	14 mm	20 mm	7,99 € / Stk
136776	G 1/8	10 mm	13 mm	6,88 € / Stk

More Pictures

