

## Datasheet for: 110817


**T-screw-in fitting G 1/8 o., for hose 6/8 mm, PA**

T-screw-in fitting G 1/8 o., for hose 6/8 mm, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA. Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	150.42
Article number	110817
EAN/barcode	 4047322029636
Your price	3,94 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Clamping ring	Polypropylene (PP)
For hose	6/8 mm
Knurled nut	Polypropylene (PP)
L1	62.0 mm
L2	20.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK742
Screw fitting body	Polyamide (PA)
Thread	G 1/8

**Variants**

Article number	Thread	For hose	Price
110817	G 1/8	6/8 mm	3,94 € / Stk

## Variants

Article number	Thread	For hose	Price
110816	G 1/8	4/6 mm	2,79 € / Stk
110818	G 1/4	4/6 mm	3,01 € / Stk
110819	G 1/4	6/8 mm	4,85 € / Stk

## More Pictures

