


Datasheet for: 112848

Elbow 2, Long, 90°, IT/IT, Rp 3/4, black malleable cast iron


Elbow 2, Long, 90°, IT/IT, Rp 3/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFB 2-34
Article number	112848
EAN/barcode	 4047322251600
Your price	3,95 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK854
Standard	acc. ISO 7-1
thread	Hot dip galvanised
Surface	Rp 3/4
Thread	

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112848	Rp 3/4	3,95 € / Stk
112847	Rp 1/2	2,70 € / Stk
112851	Rp 1 1/2	11,50 € / Stk
112849	Rp 1	5,21 € / Stk
112845	Rp 1/4	2,16 € / Stk
112852	Rp 2	16,87 € / Stk
112846	Rp 3/8	2,70 € / Stk
112850	Rp 1 1/4	9,17 € / Stk
112853	Rp 2 1/2	43,11 € / Stk
112854	Rp 3	53,53 € / Stk