

Datasheet for: 136516


Screw-on connection POM, G 1/4, for hose exterior Ø 8 mm

Screw-on connection POM, G 1/4, for hose exterior Ø 8 mm, Working pressure max. 16 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

Type number	94.014-8
Article number	136516
EAN/barcode	 4047322506151
Your price	2,81 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

For tube O.D.	8 mm
L1	33.0 mm
Material	Acetal polymer (POM)
Max. operating temperature in air	70 °C
Max. operating temperature in water	70 °C
Max. working pressure	16 bar
Min. operating temperature in air	-20 °C
Min. operating temperature in water	1 °C
Page No.	HK697
Thread	G 1/4

Variants

<i>Article number</i>	<i>Thread</i>	<i>For tube O.D.</i>	<i>Price</i>
136516	G 1/4	8 mm	2,81 € / Stk
136514	G 1/8	6 mm	2,78 € / Stk
136518	G 3/4	8 mm	3,42 € / Stk
136517	G 3/8	8 mm	3,74 € / Stk
136513	G 1/8	4 mm	2,60 € / Stk
136515	G 1/4	6 mm	3,33 € / Stk

More Pictures

