

Datasheet for: 111409


Locking screw, Hexagonal socket 3 mm, G 1/8, nickel-plated brass

Locking screw, Hexagonal socket 3 mm, G 1/8, NBR O-ring, nickel-plated brass, Max. working pressure 25 bar, Max. operating temp. 80°C. Suitable for air, water, oil, steam, etc.

Type number	233.02-N
Article number	111409
EAN/barcode	 4047322054829
Your price	0,73 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Hexagon socket head	3.0 mm
L1	9.5 mm
L2	7.0 mm
Material	Nickel-plated brass CW614N
Max. operating temperature	80 °C
Max. working pressure	25 bar
Page No.	HK778
Sealant	NBR O-ring
Thread	G 1/8 hexagon socket head

Variants

Article number	Thread	Hexagon socket head	Price
111409	G 1/8 hexagon socket head	3.0 mm	0,73 € / Stk

Variants

Article number	Thread	Hexagon socket head	Price
111408	M5 hexagon socket head	2.5 mm	0,62 € / Stk
111410	G 1/4 hexagon socket head	6.0 mm	1,02 € / Stk
111411	G 3/8 hexagon socket head	8.0 mm	1,11 € / Stk
111412	G 1/2 hexagon socket head	10.0 mm	1,66 € / Stk
111413	G 3/4 hexagon socket head	17.0 mm	4,40 € / Stk
111414	G 1 hexagon socket head	19.0 mm	5,64 € / Stk

More Pictures

