

Datasheet for: 108997


Straight push-in connector »metallica«, Plug nipple reducing

Straight push-in connector »metallica«, Plug nipple reducing 12 mm, for hose exterior Ø 10 mm, Working pressure max. 16 bar . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	867.1210
Article number	108997
EAN/barcode	 4047322391283
Your price	4,00 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	10 mm
L1	41.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK717
Plug connection	12 mm
Series	metallica
Sleeve	Nickel-plated brass

Variants
Article number
For tube O.D.
Price

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
108997	10 mm	4,00 € / Stk
108994	4 mm	2,04 € / Stk
108995	6 mm	2,33 € / Stk
108996	8 mm	2,85 € / Stk
137018	12 mm	3,73 € / Stk

More Pictures

