

Datasheet for: 136519


Thread-reducer, G 3/4, G 1/4

Thread-reducer, G 3/4, G 1/4, Working pressure max. 16 bar . Lightweight, push-in fittings distinguished by high strength, toughness, resistance to abrasion and impact resistance - ideal for a wide range of applications. All our push-in fittings made of POM have the following approvals: drinking water DVGW, KTW, FDA and NSF. Plastic and metal tubes are connected together quickly and easily. Suitable for compressed air or liquids, with good resistance to a large number of chemicals.

| | |
|-------------|---------|
| Type number | 95.3414 |
|-------------|---------|

| | |
|----------------|--------|
| Article number | 136519 |
|----------------|--------|

| | |
|-------------|--|
| EAN/barcode |  4047322506182 |
|-------------|--|

| | |
|------------|--------------|
| Your price | 2,83 € / Stk |
|------------|--------------|

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|-------------------------------------|----------------------|
| L1 | 21.0 mm |
| L2 | 35.0 mm |
| Material | Acetal polymer (POM) |
| Max. operating temperature in air | 70 °C |
| Max. operating temperature in water | 70 °C |
| Max. working pressure | 16 bar |
| Min. operating temperature in air | -20 °C |
| Min. operating temperature in water | 1 °C |
| Page No. | HK697 |
| Thread 1 | G 3/4 |
| Thread 2 | G 1/4 |

More Pictures

