


Datasheet for: 108988


Push-in T-connector »metallica«, for hose exterior Ø 4 mm

Push-in T-connector »metallica«, for hose exterior Ø 4 mm, Working pressure max. 16 bar, Operating temperature -20 °C to 150 °C . All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	849.004
Article number	108988
EAN/barcode	 4047322279154
Your price	4,07 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	4 mm
L1	34.0 mm
L2	17.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK716
Series	metallica
Sleeve	Nickel-plated brass

Variants

Article number	For tube O.D.	Price
108988	4 mm	4,07 € / Stk

Variants

<i>Article number</i>	<i>For tube O.D.</i>	<i>Price</i>
108991	10 mm	6,87 € / Stk
108990	8 mm	4,84 € / Stk
108989	6 mm	4,50 € / Stk
108993	14 mm	11,01 € / Stk
108992	12 mm	8,36 € / Stk
136782	16 mm	42,54 € / Stk

More Pictures

