

Datasheet for: 113154


Counter nut 310, IT, Rp 3/4, black malleable cast iron

Counter nut 310, IT, Rp 3/4, Operating temperature -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFG 310-34
Article number	113154
EAN/barcode	 4047322396318
Your price	0,83 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK863
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp 3/4

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
113154	Rp 3/4	0,83 € / Stk
113159	Rp 3	10,06 € / Stk
113157	Rp 2	3,77 € / Stk
113156	Rp 1 1/2	1,87 € / Stk
113158	Rp 2 1/2	8,62 € / Stk
113153	Rp 1/2	0,83 € / Stk
113151	Rp 1/4	0,90 € / Stk
113155	Rp 1	1,11 € / Stk
113152	Rp 3/8	0,90 € / Stk