


Datasheet for: 107849


Jaw coupling with hose connection, I.D. 19 (3/4"), safety collar

Jaw coupling with hose connection, I.D. 19 (3/4"), with safety collar, Malleable cast iron, galvanised and yellow passivated . Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

Type number	KT 19 SB
Article number	107849
EAN/barcode	 4047322258739
Your price	4,13 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Claw distance	42 mm
DN	15.0
For hose I.D.	19 (3/4")
H	63.0 mm
L	75.1 mm
Material	Malleable iron, zinc plated and yellow chromated
Max. operating pressure	10 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK611
Safety collar	28.5
Sealant	NBR

Variants

<i>Article number</i>	<i>DN</i>	<i>For hose I.D.</i>	<i>Safety collar</i>	<i>H</i>	<i>Price</i>
107849	15.0	19 (3/4")	28.5	63.0 mm	4,13 € / Stk
107850	19.0	25 (1")	38.0	63.0 mm	6,21 € / Stk
107848	8.5	13 (1/2")	25.0	63.0 mm	5,13 € / Stk