

Datasheet for: 110796


Angled screw-in fitting G 1/8 o., for hose 6/8 mm, PA

Angled screw-in fitting G 1/8 o., for hose 6/8 mm, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA. Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzene, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	140.52
Article number	110796
EAN/barcode	 4047322027786
Your price	2,92 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	6/8 mm
Knurled nut	Polypropylene (PP)
L1	30.0 mm
L2	23.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK742
Screw fitting body	Polyamide (PA)
Thread	G 1/8

Variants

Article number	Thread	For hose	Price
110796	G 1/8	6/8 mm	2,92 € / Stk

Variants

Article number	Thread	For hose	Price
110795	G 1/8	4/6 mm	1,63 € / Stk
110797	G 1/8	8/10 mm	4,15 € / Stk
110798	G 1/8	9/12 mm	10,85 € / Stk
110799	G 1/4	4/6 mm	2,08 € / Stk
110800	G 1/4	6/8 mm	3,19 € / Stk
110801	G 1/4	8/10 mm	5,24 € / Stk
110802	G 1/4	9/12 mm	11,05 € / Stk
110803	G 3/8	4/6 mm	3,78 € / Stk
110804	G 3/8	6/8 mm	4,01 € / Stk
110805	G 3/8	8/10 mm	6,32 € / Stk
110806	G 3/8	9/12 mm	11,58 € / Stk
110807	G 1/2	4/6 mm	4,39 € / Stk
110808	G 1/2	6/8 mm	5,27 € / Stk
110809	G 1/2	8/10 mm	6,39 € / Stk
110810	G 1/2	9/12 mm	13,78 € / Stk

More Pictures

