

Datasheet for: 108869


Straight push-in fitting »metallica« G 1/2 o., hose exterior Ø 10

Straight push-in fitting »metallica«, G 1/2 o., for hose exterior Ø 10 mm, Working pressure max. 16 bar, nickel-plated brass. Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	845.012-10
Article number	108869
EAN/barcode	 4047322278904
Your price	4,15 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For tube O.D.	10 mm
L1	31.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Outer hex	With
Page No.	HK712
Series	metallica
Sleeve	Nickel-plated brass
Thread	G 1/2
a/f	16 mm

Variants

Article number	Thread	For tube O.D.	a/f	Price
108869	G 1/2	10 mm	16 mm	4,15 € / Stk
108862	G 1/4	8 mm	13 mm	2,10 € / Stk
108861	G 1/4	6 mm	11 mm	2,07 € / Stk
108860	G 1/4	4 mm	9 mm	2,07 € / Stk
108855	M5	6 mm	Ø 10.5 mm	1,94 € / Stk
108854	M5	4 mm	Ø 9 mm	1,94 € / Stk
108856	G 1/8	4 mm	9 mm	1,94 € / Stk
108858	G 1/8	8 mm	13 mm	2,05 € / Stk
108866	G 3/8	10 mm	16 mm	3,32 € / Stk
108865	G 3/8	8 mm	13 mm	2,55 € / Stk
108857	G 1/8	6 mm	11 mm	1,94 € / Stk
108863	G 1/4	10 mm	16 mm	2,80 € / Stk
108871	G 1/2	14 mm	21 mm	6,29 € / Stk
108868	G 3/8	14 mm	21 mm	5,99 € / Stk
108859	G 1/8	10 mm	16 mm	3,72 € / Stk
108870	G 1/2	12 mm	18 mm	4,86 € / Stk
108864	G 1/4	12 mm	18 mm	3,78 € / Stk
108867	G 3/8	12 mm	18 mm	4,01 € / Stk
136774	G 1/2	16 mm	24 mm	20,52 € / Stk
136773	G 3/8	16 mm	24 mm	19,72 € / Stk

More Pictures

