

Datasheet for: 133755


Double threaded nipple 245, reducing, R 1 ET, R 3/4 ET

Double threaded nipple 245, reducing, R 1 ET, R 3/4 ET, black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFD 245-1034-S
Article number	133755
EAN/barcode	 4047322481342
Your price	1,94 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK870
Standard	acc. ISO 7-1
thread	Black
Surface	R 1
Thread 1	R 3/4
Thread 2	

Variants

Article number	Thread 1	Thread 2	Price
133755	R 1	R 3/4	1,94 € / Stk
133761	R 2	R 1 1/2	6,14 € / Stk
133749	R 3/8	R 1/4	1,46 € / Stk
133752	R 3/4	R 3/8	2,91 € / Stk
133757	R 1 1/4	R 1	3,55 € / Stk
133754	R 1	R 1/2	2,72 € / Stk
133758	R 1 1/2	R 1	5,55 € / Stk
133756	R 1 1/4	R 3/4	3,87 € / Stk
133759	R 1 1/2	R 1 1/4	5,18 € / Stk
133753	R 3/4	R 1/2	1,52 € / Stk
133763	R 2 1/2	R 2	15,52 € / Stk
133750	R 1/2	R 1/4	1,79 € / Stk
133762	R 2 1/2	R 1 1/2	10,34 € / Stk
133760	R 2	R 1 1/4	6,47 € / Stk
133751	R 1/2	R 3/8	1,55 € / Stk