

Datasheet for: 108839



L-ring piece, for hollow screw G 1/4, for hose exterior Ø 12 mm

L-ring piece, for hollow screw G 1/4, for hose exterior Ø 12 mm, Working pressure max. 16 bar, Operating temp. -20 °C to 70 °C . The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass. Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

Type number	765.014-12
Article number	108839
EAN/barcode	 4047322285834
Your price	4,22 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Stainless steel
For banjo bolt	G 1/4
For tube O.D.	12 mm
L1	28.0 mm
L2	17.0 mm
Material	Nickel-plated brass
Max. operating temperature	70 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK709
Series	click-clock
Sleeve	Hostaform

Variants

Article number	For banjo bolt	For tube O.D.	Price
108839	G 1/4	12 mm	4,22 € / Stk
108841	G 3/8	10 mm	3,67 € / Stk
108842	G 3/8	12 mm	4,26 € / Stk
108834	G 1/8	6 mm	2,36 € / Stk
108836	G 1/4	6 mm	2,76 € / Stk
108840	G 3/8	8 mm	3,45 € / Stk
108835	G 1/8	8 mm	2,62 € / Stk
108833	G 1/8	4 mm	2,49 € / Stk
108838	G 1/4	10 mm	3,31 € / Stk
108837	G 1/4	8 mm	2,80 € / Stk
108832	M5	4 mm	2,20 € / Stk

More Pictures

