


Datasheet for: 113117


Reducing sleeve 246, IT/ET, Rp 1/2, R 3/8

Reducing sleeve 246, IT/ET, Rp 1/2, R 3/8, Operating temp. -20 °C to 300 °C, black malleable cast iron, Hot-dip galvanised . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFM 246-1238
Article number	113117
EAN/barcode	 4047322253413
Your price	1,97 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK862
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread 1	Rp 1/2
Thread 2	R 3/8

Variants

Article number	Thread 1	Thread 2	Price
113117	Rp 1/2	R 3/8	1,97 € / Stk
113122	Rp 1 1/4	R 1	5,03 € / Stk
113118	Rp 3/4	R 1/2	2,70 € / Stk
113115	Rp 3/8	R 1/4	1,97 € / Stk
113123	Rp 1 1/2	R 1	6,11 € / Stk
113120	Rp 1	R 3/4	3,77 € / Stk
113119	Rp 1	R 1/2	3,60 € / Stk
113121	Rp 1 1/4	R 3/4	5,03 € / Stk
113116	Rp 1/2	R 1/4	1,97 € / Stk
113126	Rp 2	R 1 1/4	8,62 € / Stk
113125	Rp 2	R 1	10,24 € / Stk
113124	Rp 1 1/2	R 1 1/4	6,11 € / Stk
113127	Rp 2	R 1 1/2	8,79 € / Stk
113130	Rp 3	R 2 1/2	26,37 € / Stk
113129	Rp 3	R 2	21,19 € / Stk
113128	Rp 2 1/2	R 2	14,73 € / Stk