


Datasheet for: 112891


Bracket 90, 90°, IT/IT, Rp 1/2, black malleable cast iron

Bracket 90, 90°, IT/IT, Rp 1/2, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised, DIN EN 10242 . Acc. to DIN EN 10242 (formerly DIN 2950) The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water; they are also protected against rust. These malleable iron fittings are used in machine construction, exterior lines, cold water lines and heating lines. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 90-12
Article number	112891
EAN/barcode	 4047322252072
Your price	0,93 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK856
Standard thread	acc. ISO 7-1
Surface	Hot dip galvanised
Thread	Rp 1/2

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
112891	Rp 1/2	0,93 € / Stk
112889	Rp 1/4	1,29 € / Stk
112893	Rp 1	2,08 € / Stk
112890	Rp 3/8	1,23 € / Stk
112894	Rp 1 1/4	3,55 € / Stk
112896	Rp 2	6,79 € / Stk
112892	Rp 3/4	1,37 € / Stk
112895	Rp 1 1/2	5,54 € / Stk
112897	Rp 2 1/2	17,78 € / Stk
112898	Rp 3	25,69 € / Stk