

Datasheet for: 111344


Reducing nipple, R 1/2 o., G 1/4 i., AF 22, nickel-plated brass

Reducing nipple, R 1/2 o., G 1/4 i., AF 22, nickel-plated brass, Max. working pressure 25 bar, Max. operating temperature 150 °C . Suitable for air, water, oil, steam, etc.

| | |
|----------------|--|
| Type number | 235.05/N |
| Article number | 111344 |
| EAN/barcode |  4047322273091 |
| Your price | 2,01 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|----------------------------|
| Female thread | G 1/4 |
| L1 | 20.0 mm |
| L2 | 14.0 mm |
| Male thread | R 1/2 |
| Material | Nickel-plated brass CW614N |
| Max. operating temperature | 150 °C |
| Max. working pressure | 25 bar |
| Page No. | HK775 |
| a/f | 22 mm |

Variants

| Article number | Male thread | Female thread | a/f | Price |
|----------------|-------------|---------------|-------|--------------|
| 111344 | R 1/2 | G 1/4 | 22 mm | 2,01 € / Stk |
| 111343 | R 1/2 | G 1/8 | 22 mm | 2,01 € / Stk |
| 111345 | R 1/2 | G 3/8 | 22 mm | 2,05 € / Stk |
| 111342 | R 3/8 | G 1/4 | 17 mm | 1,17 € / Stk |

Variants

| Article number | Male thread | Female thread | a/f | Price |
|----------------|-------------|---------------|-------|--------------|
| 111346 | R 3/4 | G 3/8 | 27 mm | 3,43 € / Stk |
| 111341 | R 3/8 | G 1/8 | 17 mm | 1,09 € / Stk |
| 111340 | R 1/4 | G 1/8 | 14 mm | 0,86 € / Stk |
| 111349 | R 1 | G 3/4 | 34 mm | 7,55 € / Stk |
| 111348 | R 1 | G 1/2 | 34 mm | 5,57 € / Stk |
| 111347 | R 3/4 | G 1/2 | 27 mm | 3,60 € / Stk |

More Pictures

