

Datasheet for: 110818


T-screw-in fitting G 1/4 o., for hose 4/6 mm, PA

T-screw-in fitting G 1/4 o., for hose 4/6 mm, Working pressure max. 10 bar (20 °C)/max. 1 bar (60 °C), PA. Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	150.51
Article number	110818
EAN/barcode	 4047322029650
Your price	3,01 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	4/6 mm
Knurled nut	Polypropylene (PP)
L1	54.0 mm
L2	27.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK742
Screw fitting body	Polyamide (PA)
Thread	G 1/4

Variants

Article number	Thread	For hose	Price
110818	G 1/4	4/6 mm	3,01 € / Stk

Variants

Article number	Thread	For hose	Price
110816	G 1/8	4/6 mm	2,79 € / Stk
110817	G 1/8	6/8 mm	3,94 € / Stk
110819	G 1/4	6/8 mm	4,85 € / Stk

More Pictures

