

Datasheet for: 107771


**GEKA threaded piece, rigid, bright brass, G 1 exterior**

GEKA threaded piece, rigid, bright brass, G 1 exterior,  
 Operating pressure max. 40 bar, Medium / ambient temp.  
 -10 °C to 90 °C . Claw couplings (claw distance: 40 mm) made  
 of brass for water, industrial, mortar, suction and discharge  
 hoses. Suitable for a wide range of applications, e.g.  
 industrial plant engineering, civil and structural engineering,  
 environmental engineering, manual trades, domestic water  
 engineering, horticulture and landscaping, agriculture and  
 forestry, etc. Available in a rigid or 360° swivelling version.  
 The two systems can also be easily coupled to one another!

Type number	K 113 A
Article number	107771
EAN/barcode	 4047322133005
Your price	4,26 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1 ET
Max. ambient temperature	90 °C
Max. medium temperature	90 °C
Max. operating pressure	40 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK607
Sealant	NBR

**Variants**

<i>Article number</i>	<i>Connection</i>	<i>Price</i>
107771	G 1 ET	4,26 € / Stk
107767	G 1/4 ET	6,27 € / Stk
107768	G 3/8 ET	4,39 € / Stk
107769	G 1/2 ET	3,96 € / Stk
107770	G 3/4 ET	4,13 € / Stk
107772	G 1 1/4 ET	6,15 € / Stk
107773	G 1 1/2 ET	7,78 € / Stk