

Datasheet for: 111345


Reducing nipple, R 1/2 o., G 3/8 i., AF 22, nickel-plated brass

Reducing nipple, R 1/2 o., G 3/8 i., AF 22, nickel-plated brass, Max. working pressure 25 bar, Max. operating temperature 150 °C . Suitable for air, water, oil, steam, etc.

Type number	235.06/N
Article number	111345
EAN/barcode	 4047322273114
Your price	2,05 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Female thread	G 3/8
L1	20.0 mm
L2	14.0 mm
Male thread	R 1/2
Material	Nickel-plated brass CW614N
Max. operating temperature	150 °C
Max. working pressure	25 bar
Page No.	HK775
a/f	22 mm

Variants

Article number	Male thread	Female thread	a/f	Price
111345	R 1/2	G 3/8	22 mm	2,05 € / Stk
111343	R 1/2	G 1/8	22 mm	2,01 € / Stk
111344	R 1/2	G 1/4	22 mm	2,01 € / Stk
111342	R 3/8	G 1/4	17 mm	1,17 € / Stk

Variants

Article number	Male thread	Female thread	a/f	Price
111346	R 3/4	G 3/8	27 mm	3,43 € / Stk
111341	R 3/8	G 1/8	17 mm	1,09 € / Stk
111340	R 1/4	G 1/8	14 mm	0,86 € / Stk
111349	R 1	G 3/4	34 mm	7,55 € / Stk
111348	R 1	G 1/2	34 mm	5,57 € / Stk
111347	R 3/4	G 1/2	27 mm	3,60 € / Stk

More Pictures

