


Datasheet for: 133767


Double thr. nipple 280 ET/ET R 3/4 black malleable iron fitting

Double threaded nipple 280, ET/ET, R 3/4, black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFD 280-34-S
Article number	133767
EAN/barcode	 4047322481632
Your price	0,97 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK870
Standard thread	acc. ISO 7-1
Surface	Black
Thread	R 3/4

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133767	R 3/4	0,97 € / Stk
133771	R 2	4,60 € / Stk
133768	R 1	1,39 € / Stk
133772	R 2 1/2	8,73 € / Stk
133765	R 3/8	1,17 € / Stk
133764	R 1/4	1,17 € / Stk
133766	R 1/2	0,79 € / Stk
133769	R 1 1/4	2,40 € / Stk
133770	R 1 1/2	2,77 € / Stk