

Datasheet for: 110840


Straight bulkhead connector, M10x1, for hose 4/6 mm, AF 14, PA

Straight bulkhead connector, M10x1, for hose 4/6 mm, AF 14, Working pressure max. 10 bar (20 °C)/max. 10 bar (60 °C), PA . Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	140.31
Article number	110840
EAN/barcode	 4047322027595
Your price	2,07 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	4/6 mm
Knurled nut	Polypropylene (PP)
L1	53.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK744
Screw fitting body	Polyamide (PA)
Thread	M10x1.0
a/f	14 mm

Variants

Article number	Thread	For hose	a/f	Price

Variants

Article number	Thread	For hose	a/f	Price
110840	M10x1.0	4/6 mm	14 mm	2,07 € / Stk
110841	M14x1.5	6/8 mm	19 mm	3,15 € / Stk
110842	M16x1.5	8/10 mm	22 mm	4,01 € / Stk
110843	M18x1.5	9/12 mm	24 mm	8,82 € / Stk

More Pictures

