

## Datasheet for: 107860


**Jaw coupling with interior thread, G 3/4, DN 20**

Jaw coupling with IT, G 3/4, DN 20, Malleable cast iron, galvanised and yellow passivated, Operating pressure max. 10 bar . Universal standard coupling for compressed air lines on construction sites or in industry; standard type according to DIN 3489, used worldwide in a very wide range of applications. - Robust couplings made of malleable iron, zinc plated and yellow chromated - Chrome VI-free, with double safety lock - 100% couple test and secure connection

Type number	KI 34
Article number	107860
EAN/barcode	 4047322259071
Your price	4,33 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Claw distance	42 mm
DN	20.0
H	63.0 mm
L	38.0 mm
Material	Malleable iron, zinc plated and yellow chromated
Max. operating pressure	10 bar
Max. operating temperature	95 °C
Min. operating temperature	-40 °C
Page No.	HK611
Sealant	NBR
Thread	G 3/4
a/f	32 mm

## Variants

<i>Article number</i>	<i>DN</i>	<i>Thread</i>	<i>a/f</i>	<i>Price</i>
107860	20.0	G 3/4	32 mm	4,33 € / Stk
107861	20.0	G 1	40 mm	5,13 € / Stk
107858	15.0	G 3/8	22 mm	5,13 € / Stk
107859	19.0	G 1/2	27 mm	5,40 € / Stk