


Datasheet for: 133680


T-piece 130, IT/IT/IT, Rp 1, T-branch Rp 1/2

T-piece 130, IT/IT/IT, Rp 1, T-branch reducing Rp 1/2, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFT 130-1012-S
Article number	133680
EAN/barcode	 4047322480918
Your price	3,08 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK868
Standard	acc. ISO 7-1
thread	Black
Surface	Rp 1
Thread 1	Rp 1
Thread 2 Reduced branch tee	Rp 1/2
Thread 3	Rp 1

Variants

Article number	Thread 1	Thread 2 Reduced branch tee	Thread 3	Price
133680	Rp 1	Rp 1/2	Rp 1	3,08 € / Stk
133678	Rp 1/2	Rp 3/8	Rp 1/2	1,94 € / Stk
133692	Rp 2	Rp 1 1/2	Rp 2	10,57 € / Stk
133684	Rp 1 1/4	Rp 1	Rp 1 1/4	4,48 € / Stk
133689	Rp 2	Rp 1/2	Rp 2	9,38 € / Stk
133679	Rp 3/4	Rp 1/2	Rp 3/4	2,11 € / Stk
133685	Rp 1 1/2	Rp 1/2	Rp 1 1/2	5,99 € / Stk
133682	Rp 1 1/4	Rp 1/2	Rp 1 1/4	4,48 € / Stk
133686	Rp 1 1/2	Rp 3/4	Rp 1 1/2	5,99 € / Stk
133683	Rp 1 1/4	Rp 3/4	Rp 1 1/4	4,48 € / Stk
133687	Rp 1 1/2	Rp 1	Rp 1 1/2	5,99 € / Stk
133691	Rp 2	Rp 1	Rp 2	9,38 € / Stk
133681	Rp 1	Rp 3/4	Rp 1	3,08 € / Stk
133690	Rp 2	Rp 3/4	Rp 2	9,38 € / Stk
133688	Rp 1 1/2	Rp 1 1/4	Rp 1 1/2	8,20 € / Stk