

Datasheet for: 110769


Straight screw-in fitting, G 1/8 o., for hose 4/10 mm, AF 19, PA

Straight screw-in fitting, G 1/8 o., for hose 4/10 mm, AF 19, Working pressure max. 10 bar (20°C)/max. 1 bar (60°C), PA . Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering. Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

Type number	120.13
Article number	110769
EAN/barcode	 4047322021708
Your price	4,34 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Clamping ring	Polypropylene (PP)
For hose	8/10 mm
Knurled nut	Polypropylene (PP)
L1	45.0 mm
L2	12.0 mm
Max. Operating pressure at 20 °C	10.0 bar
Max. Operating pressure at 60 °C	1.0 bar
Page No.	HK741
Screw fitting body	Polyamide (PA)
Thread	G 1/4
a/f	19 mm

Variants

Article number	Thread	For hose	a/f	Price
110769	G 1/4	8/10 mm	19 mm	4,34 € / Stk
110763	G 1/8	4/6 mm	14 mm	1,53 € / Stk
110764	G 1/8	6/8 mm	17 mm	2,56 € / Stk
110765	G 1/8	8/10 mm	19 mm	3,96 € / Stk
110766	G 1/8	9/12 mm	22 mm	7,33 € / Stk
110767	G 1/4	4/6 mm	17 mm	1,87 € / Stk
110768	G 1/4	6/8 mm	17 mm	2,94 € / Stk
110770	G 1/4	9/12 mm	22 mm	8,69 € / Stk
110771	G 3/8	4/6 mm	22 mm	3,01 € / Stk
110772	G 3/8	6/8 mm	22 mm	3,51 € / Stk
110773	G 3/8	8/10 mm	22 mm	5,75 € / Stk
110774	G 3/8	9/12 mm	22 mm	8,32 € / Stk
110775	G 1/2	4/6 mm	27 mm	4,16 € / Stk
110776	G 1/2	6/8 mm	27 mm	4,82 € / Stk
110777	G 1/2	8/10 mm	27 mm	6,09 € / Stk
110778	G 1/2	9/12 mm	27 mm	8,88 € / Stk

More Pictures

