

## Datasheet for: 108910


**Push-in L-fitting »metallica« rotating, R 1/8 o., hose ext. Ø 6**

Push-in L-fitting »metallica«, rotating, R 1/8 o., for hose exterior Ø 6 mm, Working pressure max. 16 bar, nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion; all fittings in this series can thus also be used at high temperatures (medium compressed air).

Type number	8854.018-6
Article number	108910
EAN/barcode	 4047322279420
Your price	4,36 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Clamping ring	Stainless steel
For tube O.D.	6 mm
L1	21.0 mm
L2	20.0 mm
Material	Nickel-plated brass
Max. operating temperature	150 °C
Max. working pressure	16 bar
Min. operating temperature	-20 °C
Page No.	HK713
Series	metallica
Sleeve	Nickel-plated brass
Thread	R 1/8
a/f	13 mm

## Variants

Article number	Thread	For tube O.D.	a/f	Price
108910	R 1/8	6 mm	13 mm	4,36 € / Stk
108917	R 3/8	10 mm	18 mm	6,21 € / Stk
108915	R 1/4	10 mm	16 mm	5,34 € / Stk
108916	R 3/8	8 mm	18 mm	5,69 € / Stk
108912	R 1/4	4 mm	14 mm	4,52 € / Stk
108913	R 1/4	6 mm	14 mm	4,61 € / Stk
108911	R 1/8	8 mm	13 mm	4,36 € / Stk
108909	R 1/8	4 mm	13 mm	4,22 € / Stk
108914	R 1/4	8 mm	14 mm	4,75 € / Stk
108919	R 1/2	12 mm	22 mm	10,07 € / Stk
108918	R 3/8	12 mm	20 mm	8,76 € / Stk
137010	R 3/8	14 mm	20 mm	10,56 € / Stk
137011	R 1/2	14 mm	22 mm	11,25 € / Stk

## More Pictures

