

Datasheet for: 107930


Tempered plug-on connector DN 6, Brass, Hose connection 9 mm

Tempered plug-on connector DN 6, Brass 2.0401, Hose connection 9 mm, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C . Compatible with HASCO Z 8 system. For temperature control applications involving hot or cold water or heat transfer oil, e.g. for cooling circuits on plastics processing machines. Optionally with free passage, one or both sides sealing. Female-threaded couplings and plugs with female-threaded PTFE seal.

Type number	270.601
Article number	107930
EAN/barcode	 4047322258203
Your price	1,05 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Ball	Stainless steel
Hose connection	9 mm
Length	39.5 mm
Material	Brass 2.0401
Max. ambient temperature	160 °C
Max. medium temperature	160 °C
Max. operating pressure	15 bar
Medium	Air, water, oil, vacuum
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK615
Retaining ring	Stainless steel
Sealant	FPM (PTFE coated)
Spring	Stainless steel