

Datasheet for: 133666


Bracket 121, 45°, Rp 1 IT, R 1 ET, black malleable iron fitting

Bracket 121, 45°, Rp 1 IT, R 1 ET, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1 . According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology. Working minimal temperature = -20 °C; 25 bar. Working pressure for temperature range from -20 °C to 120 °C: 25 bar. Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Type number	TFW 121-10-S
Article number	133666
EAN/barcode	 4047322480673
Your price	4,37 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Material	Black malleable iron B350-10, design symbol A
Max. temperature range	300 °C
Min. temperature range	-20 °C
Page No.	HK868
Standard thread	acc. ISO 7-1
Surface	Black
Thread	Rp/R 1

Variants

<i>Article number</i>	<i>Thread</i>	<i>Price</i>
133666	Rp/R 1	4,37 € / Stk
133665	Rp/R 3/4	2,91 € / Stk
133668	Rp/R 1 1/2	8,41 € / Stk
133669	Rp/R 2	11,31 € / Stk
133667	Rp/R 1 1/4	7,76 € / Stk
133663	Rp/R 3/8	2,36 € / Stk
133664	Rp/R 1/2	2,11 € / Stk